

M & M Barns Exterior Door Quote Sheet

1. Sizing: Sizing is noted as follows: 2/6= 30", 2/8=32", 3/0=36", 3/6=42". Standard height is 80" or 6/8
Circle one (2/6 x 6/8, 2/8 x 6/8, 3/0 x 6/8, 3/6 x 6/8)
2. Inswing or Outswing?
3. Jamb size (4-9/16" for 2x4 walls or 6-9/16" for 2x6 walls). Wood or Composite?
4. Brickmold attached? (Wood or Vinyl)
5. Steel slab, Smooth Paintable Fiberglass, or Textured Paintable/stainable fiberglass?)
6. Light Options
 - No Glass (6-Panel or Flush Slab)
 - Colonial 22x36 One Light (no grids, 2-Panel Bottom)
 - Colonial 22x36 Nine Light (internal grids, 2-Panel bottom)
 - 22x64 15 Light (internal grids)
 - 22x64 Full Light (no grids)
 - Venting 2-Light (2-Panel bottom)
 - Sunburst (Flush or 4-Panel slab)
 - Medium oval light
 - Large oval light
 - 15x15 Light (flush slab)
 - Other (From ODL catalog, see Odl.com. Only certain lights are stocked)

Note: Not all slab/light combinations may be possible, but we are happy to check for you!
7. Standard bore (for regular knob?) Additionally: deadbolt prep?
8. Sill: Standard, adjustable, or ADA/handicap sill?
9. For double (patio) doors, please specify which side will be active. Other side will be pinned and can only open once the active door is opened.

Questions, just call, email, or fax us!